



900T Pull Type

Standard unit may not be exactly as shown.



900T Pull Type

Standard Equipment

- Two Patented Freestanding Vertical Cutting Augers
- Manual Restrictor Plates
- (2) Heavy-Duty, Two-Stage Planetary Drives
- Replaceable Forage Cutting Blades (10)
- 540 or 1000 rpm PTO
- Heavy-Duty Tubular Steel Frame
- 3/4" M/S Floor
- 1/4" AR200 Walls
- 5/8" AR200 Lower Auger Flighting
- Front Centre Door with 8' Flat Conveyor
- Ultra Wear Kicker Plates
- Removable Heavy Duty Hitch Jack
- 4 pt DG Stad 04 Plus Scale with Remote Port and 12 Recipe Programming Capability
- 12 Volt Battery
- (4) 11R/22.5, 16 Ply Truck Tires with Budd Wheels and HD Axle

Model 900T Pull-Type

	Imperial	Metric
Empty Weight	16,255 lbs.	7,373 kg
Max. Payload At 5mph / 8km/h	24,000 lbs.	10,908 kg
Height	117 in.	297 cm
W/10" Extension	127 in.	322 cm
Overall Width	123 in.	312 cm
Overall Length	273 in.	693 cm
Min. HP Req.	130	130
Capacity W/10" Extension	849 cu. ft.	24.1 m ³
Capacity Struck Level	739 cu. ft.	20.9 m ³

*Discharge Ground Clearance (Inches/cm)

Side Door Conveyor	36" Fold	44" Fold	72" Fold	96" Fold	Fixed Chute
900T	44"/112cm	48"/122cm	60"/152cm	70"/178cm	30"/176cm
Front Centre Door Conveyor	Flat	Dogleg	Ext. Dogleg	42" Fold	54" Fold
900T	30"/76cm	42"/107cm	53"/135cm	47"/119cm	52"/132cm

